

SENSOR RETROFIT FLUSHOMETER COMPARISON CHART



SLOAN®

Optima Plus® Single Flush Side Mount Retrofit

Optima Plus® Dual Flush Side Mount Retrofit

SLOAN® Optima® Systems SMOOTH® Side-Mount Retrofit

Retrofit Side Mount with Metal Cover

| | | | | |
|--------------------------|---|---|---|---|
| Model Number | EBV-500-A | EBV-550-A | EBV-200-A | EBV-89-A |
| Code Number | 3325500 | 3325501 | 3325201 | 0325105 |
| Description | Battery-Powered, Sensor-Activated, Single-Flush Retrofit Conversion Kit for Exposed Closet or Urinal Flushometers | Battery-Powered, Sensor-Activated, Dual-Flush Retrofit Conversion Kit for Exposed Closet Flushometers | Battery-Powered, Sensor Activated Retrofit Unit for Exposed Closet and Urinal Flushometers | Battery-Powered, Sensor-Operated Retrofit Conversion Kit for Exposed Closet and Urinal Flushometers |
| Installation Type | Side Mount Retrofit | | Over-the-handle Retrofit | Side Mount Retrofit |
| Sensor Type | Multi-Lobular Infrared Sensor / Infrared Convergence Type Object Lock Detection | Multi-Lobular Infrared Sensor featuring Dual Flush Volume / Infrared Convergence Type Object Lock Detection | OPTIMA® SMOOTH™ Infrared Sensor | OPTIMA® Battery Powered Infrared Sensor / Infrared Convergence Type Object Lock Detection |
| Sensor Range | Factory Set at 22-42 inches Can be converted to Urinal Range setting of 15-30 inches | Factory Set at 22-42 inches | • Normal Range of 22-42 inches with 2-3 second flush delay. • Reduced Range (for Water Closets) of 20-26 inches with 2-3 second flush delay. • Reduced Range (for Urinals) of 20-26-inches with 1-2 second flush delay. | Nominal 8” - 54” (203 mm - 1372 mm) Factory Set at 24” (610 mm) |
| Indicator Lights | User in View and Low Battery | | | |
| True Mechanical Override | Non-Hold-Open True Mechanical Override Full Flush Button | Non-Hold-Open True Mechanical Override Full Flush Button | Non-Hold-Open True Mechanical Override Full Flush Button | None |
| Smart Sense Technology | Included | | Not Included | |
| Service Mode | Included | | Not Included | |
| Sentinel Flush Mode | 72 Hour Sentinel Flush | | | 24 Hour Sentinel Flush |
| Operating Pressure | 25-80 PSI | | | 15-100 PSI |
| Application | Closet and Urinal Applications | Closet Applications | Closet and Urinal Applications | |
| Feature | Best Seller | Water Saving Option | Easy Installation, Battery Saving Technology | Most Compact |
| Battery/Type | Four (4) “C” Alkaline Batteries Included | | | |
| Hardwire Option | Yes, Part #87854 | Yes, Part #87853 | Yes, Part #86530 | No |
| View Unit Listing | Click Here | Click Here | Click Here | Click Here |
| Equiparts Part Number | #85606 | #85605 | #08825 | #08532 |

Website: equiparts.com Phone Number: 800-442-6622